

CE ISO-9001 TUV NORD

Grindermac series

LMC
LEADERMAC

LMC 2023.02

LMC
LEADERMAC

LEADERMAC MACHINERY CO., LTD.

No. 20, Lane 662, Sec 1, Sha-Tien Rd., Dadu District, Taichung, Taiwan 432403

TEL: +886-4-2693-7599

<https://www.leadermac.com>

FAX: +886-4-2693-7588 / 2693-7589

e-mail: info@leadermac.com • sales@leadermac.com



Leadership Through Performance
and Reliability

Grindermac series
G320A / G320B / G320P / G320PS

LEADERMAC MACHINERY CO., LTD.

Quality Features Add More Value to Your Production

LMC
LEADERMAC

series G320A / G320B

Leadership Through Performance and Reliability

OUTSTANDING FEATURES:

- Cutter rotation is automatically controlled by PLC for high accuracy.
- Grinding head movement is automatically controlled by PLC, ensuring high grinding accuracy.
- Humanified touch-sensing screen allows for convenient operation.
- Multiple micro-switches protection upgrades operational safety.
- Hydraulic system controls the slide movement rightward / leftward, featuring maximum stability.
- Automatic or manual movement of slide is quick to change.
- The entire machine is thoroughly protected by safety guards to achieve higher safety.
- Fast cutterhead change saves considerable time while upgrading efficiency.
- The control panel offers simple setting of tool parameters that saves cutter setting time.
- Movable working light for added convenience.

G320B

G320A



NC CONTROLLER



G320B Beveled Knife Back Grinding
(ex. Solid cutter, Finger jointer knife)



G320B Knife Edge Grinding
(Movable straight knife)



G320A Knife Edge Grinding
(Movable straight knife)

Automatic Cutter Grinder

The Grindermac G320A and G320B automatic cutter grinder is an advanced grinder, featuring fully automatic grinding operation. With the PLC control, high grinding accuracy is obtainable.

G320P / G320PS series

OUTSTANDING FEATURES:

- The profile cutter grinder is designed for grinding knife profile and sharpening applications. Especially ideal for grinding profile-cutters used for cutting decoration strips.
- Allows for grinding a cutterhead with 2, 4, 6, 8 or more knives. The ground cutterhead can be directly mounted on the machine without need of further adjustment of knives.
- SPEED CHANGE CONTROL: Can be equipped with speed control for adjusting grinding wheel speed suitable for various types of knives.
- ROTARY TYPE TRACING ROD ASSEMBLY: Choice of various shapes of tracing rod to suit complicated knife profiles.
- CURVE SHAPED SLIDE: When changing grinding angle, it is not necessary to dress the grinding wheel to return to dressing reference and adjust gap of tool rest.
- When the grinding wheel diameter decreases, it is convenient to adjust the gap of tool rest.
- GRINDING WHEEL DRESSER: Provides fast dressing of grinding wheel to a shape complying with that of the tracing rod. Also suitable for correcting wear of the grinding wheel. When the grinding wheel diameter decreases, no additional calibration is required.
- GRINDING WHEEL CLAMP AND MICROMETRIC ADJUSTMENT OF WHEEL ARBOR: Provide fast adjustment of grinding wheel to keep it at the original dressing position.
- TWO-DIRECTION POSITIONING OF ARBOR: This function permits fast positioning when mounting cutterhead on the arbor. This is combined with the positioning of template support to eliminate further calibration.
- TILTING GRINDING RESET DEVICE: It allows for accurate and fast positioning after tilting grinding has been performed.
- COOLING SYSTEM: It prevents knife from burning during grinding. Also suitable for removing powder and chips during grinding.
- WASHING DEVICE: Provides for convenient cleaning on grinding table.
- The machine is conveniently lifted or moved by a forklift.



G320PS Profile knife grinding



G320PS Straight knife grinding



G320PS Multiple tracing rods allow for accurate and convenient grinding



G320PS Grinding wheel dressing



G320P

- For profile knives.



G320PS

- For profile and straight knives.
- TWO MACHINES IN ONE: This machine is also capable of grinding various straight knives. Easy to convert without need to change parts.
- OPTIONAL POWERED ADJUSTMENT: This function eliminates manual adjustment, enhancing operation convenience.



G320P Profile knife grinding



G320P Multiple tracing rods allow for accurate and convenient grinding

Tool Calibration Device

A tool calibration device can be supplied for the convenient and accurate calibration of each cutterhead, thus ensuring perfect cutterhead running.



SPECIFICATIONS

MODEL	G320A	G320B
Max. length of cutterhead		
Conventional cutterhead (by nut locking)	320 mm (12.6")	320 mm (12.6")
Hydraulic cutterhead (by hydraulic bushing locking)	320 mm (12.6")	320 mm (12.6")
Max. diameter of cutter	320 mm (12.6")	320 mm (12.6")
Min. diameter of cutter	125 mm (5")	125 mm (5")
Max. number of knives	32	32
Grinding wheel		
Diameter	175 mm (6.9")	175 mm (6.9")
Bore	25 mm (1")	20 mm (0.79")
Spindle speed	3000 rpm Max	1000~6000 rpm
Motors		
Grinding wheel arbor	1.5 Kw (2 HP)	3.75 Kw (5 HP)
Coolant pump	0.188 Kw (0.25 HP)	0.188 Kw (0.25 HP)
Hydraulic motor	0.75 Kw (1 HP)	0.75 Kw (1 HP)
Cooling system		
Coolant tank capacity - Max.	28 liters (6.15 gallons)	23 liters (6.08 gallons)
Coolant tank capacity - Min.	16 liters (3.5 gallons)	11 liters (2.91 gallons)
Machine Dimensions		
Length	1905 mm (75")	1985 mm (78.1")
Width	1100 mm (43.3")	1645 mm (64.8")
Height	1500 mm (59")	1800 mm (74.8")
Worklamp	20 w	20 w

●All specifications, dimensions and design characteristics are subject to change without notice.

SPECIFICATIONS

MODEL	G320P	G320PS
Maximum length of cutterhead		
Using locking collars	320 mm (12.6")	320 mm (12.6")
Hydro locking block	320 mm (12.6")	320 mm (12.6")
Maximum cutting circle		
Profile grinding	350 mm (13.8")	350 mm (13.8")
Straight knife	-	300 mm (11.8")
Minimum cutting circle		
All types	70 mm (2.75")	70 mm (2.75")
Maximum depth of profile	40 mm (1.57")	40 mm (1.57")
Grinding wheels for profile grinding		
Diameter	230 mm (9")	230 mm (9")
Width	5 mm (0.197")	5 mm (0.197")
Dressed width	4.7 mm or 3.0 mm	4.7 mm or 3.0 mm
Bore	60 mm (2.36")	60 mm (2.36")
For solid profile (C.B.N. type)		
Diameter options	-	100 mm (4")
Bore	-	20 mm (0.787")
Spindle Speeds (Infinitely variable)		
Profile grinding spindle	1500-3000 rpm	1500-3000 rpm
Straight knife spindle	-	3000-6000 rpm
Motor Outputs		
Profile grinding spindle	1.5 Kw (2 HP)	1.5 Kw (2 HP)
Straight knife spindle	-	0.75 Kw (1 HP)
Head tilt	-	0.025 Kw (0.03 HP)
Coolant pump	0.188 Kw (0.25 HP)	0.188 Kw (0.25 HP)
Coolant System		
Tank capacity maximum	36 liters (8 gallons)	36 liters (8 gallons)
Tank capacity minimum	18 liters (4 gallons)	18 liters (4 gallons)
Machine Dimensions		
Depth	1150 mm (45.3")	1100 mm (43.3")
Width	1150 mm (45.3")	1150 mm (45.3")
Height	1680 mm (66.2")	1505 mm (59.3")
Worklamp	20 w	20 w

●All specifications, dimensions and design characteristics are subject to change without notice.